



## Technical Data Sheet

### SealGreen SGR1500 Professional Mastic Remover

Ideal for use in occupied areas like post offices, schools, hospitals and other public places where safety is important. **SealGreen SGR1500** removes newer mastics, layered adhesives and even glues 50+ years old, using the power of soybeans. It's the first product to pass both performance and environmental safety tests by the USPS for the removal of mastic containing asbestos!

Contractors find that SealGreen SGR1500 works more efficiently, saves time, and helps create a safer restoration site compared to traditional hazardous chemical mastic removers.

#### Coverage:

One gallon will generally cover between 100-200 square feet. Many customers report getting up to 200 sqft per gallon.

#### Test Area:

Due to variances in surfaces and conditions, always test in a small, inconspicuous area before using on complete project.

#### Application:

Apply SealGreen SGR1500 Mastic Remover directly on the concrete surface. Spread SealGreen SGR1500 around with a straw broom, long handled brush, thick nap roller, or squeegee using light pressure. If applying to mastic with trowel ridges, cover all trowel ridges with product. Allow SealGreen SGR1500 to sit until mastic softens. (Generally asbestos/black mastics will soften in 1-2 hours, and vinyl or acrylic mastics will soften in 4-8 hours.) After mastic has softened, remove with a long handled scraper or squeegee. Reapply if necessary.

#### Clean Up:

Clean remaining thin residue with SealGreen Oil Cleaner Degreaser using a scrub brush and/or mop or power washer. Allow surface to dry before further preparations.

#### Residue Test:

After rinsing, apply water to various small areas on the concrete and rub with fingers. If water turns cloudy white, it indicates there is SealGreen SGR1500 remaining on the surface. Repeat clean up steps and retest.

#### Usage Tips from the Pros:

- Use a commercial sprayer or metal watering can to

apply SealGreen SGR1500 in large areas.

- Protect floor drains and areas where product would naturally flow on uneven surfaces with sand, Oil-Dri®, or kitty litter.
- A rotary floor machine used on a low RPM speed helps during the water/degreaser clean up steps. Use only after scraping up softened mastic.

#### Biodegradable:

Meets or exceeds ASTM standards

#### Precautions:

Concrete surfaces may darken with use of SealGreen SGR1500. For porous and/or cracked substrates, use a commercial absorbent to help in pick-up of mastic residue. Always use care to prevent overspray from getting on surfaces other than the one being prepped or cleaned. Do not use SealGreen SGR1500 on wood surfaces. Use rotary machine only after scraping up softened mastic.

#### Warnings:

Causes mild skin irritation. Causes eye irritation. May be harmful if swallowed. Keep out of reach of children.

#### Flash Point:

Above 425°F (218.33°C)

#### pH Level:

6.65 pH of 1/10 wt/wt solution in soft water

#### VOC (Volatile Organic Compounds):

2.3%, .06 lb/g, 20 g/l. California and OTC Compliant

#### Ingredients:

Soy Ester, Proprietary Surfactant Blend

**Safe for Use On:** Concrete

**Do Not Use On:** Wood surfaces

#### Packaged:

Quart, Gallon, Five Gallon, 55 Gallon Drum

#### Coverage:

Horizontal - Up to 120 sq. ft. per gallon  
Vertical - Up to 100 sq. ft. per gallon

#### For More Information Contact:

ReUse Concrete Sealing Specialists, LLC  
16072 Foster St, Overland Park, KS 66085  
913-681-3451 - [www.sealgreen.com](http://www.sealgreen.com)